	PRODUCT COMPARISON			
	PPA500	PPA1500	PPA4500	PPA5500
Basic Accuracy				
V, A rdg error	0.05%	0.05%	0.03%	0.01%
Power rdg error	0.10%	0.10%	0.04%	0.03%
Phase Options				
nternal	1~3	1~3	1~3	1~3
laster/Slave operation	—	—	$4 \sim 6$	4~6
andwidth				
0 & 30A Shunt	$ m DC\sim500 kHz$	$ m DC \sim 1 MHz$	-	-
0 & 30A Shunt	_	-	$ m DC\sim 2MHz$	DC ~ 2MHz
0A Shunt	_	_	$ m DC \sim 1 MHz$	DC ~ 1MHz
oltage Input				
lax input voltage	2500Vpk	2500Vpk	3000Vpk	3000Vpk
lo. of ranges	8	8	8	9
Direct Current Input				
.0Arms model	-	-	0	0
0Arms model	0	0	_	-
0Arms model	0	0	0	0
0Arms model	—	-	0	0
lo. of ranges	8	8	8	9
eatures				
Scope and Graph Modes	—	0	0	0
JSB Memory port	0	0	0	0
AN Port	<b>O</b>	0	0	0
SPIB Port	<b>O</b>	$\circ$	<u>o</u>	0
S232 Port	0	0	0	0
Real time clock	0	0	0	0
9in Rack mount option	<b>O</b>	<u> </u>		<b>O</b>
orque and Speed	—	—	0	0
EC61000 Mode	—	-	-	0
WM Motor Drive Mode	—	• (Via Parallel Filtering Options)	0	0
Scilloscope/Graphic	—	0	0	<b>O</b>
ransformer Mode	—	—	0	0
WM Filter Options	—	2	7	7
Speed/Harmonics/Sec	300/sec	300/sec	600/sec	1800/sec
	4 Parameters	4 Parameters	16 Parameters	16 Parameters
nternal Datalogging	11 di difictorio			
	16000	16000	16000	10M
atalog Records			-	10M
Datalog Records BD0100.1.8 Mode		16000	16000 — 200MB	
Datalog Records ABD0100.1.8 Mode Internal Memory	16000 —	16000 —	-	0
Datalog Records BD0100.1.8 Mode Internal Memory Iarmonics	16000 — 192kB	16000 — 192kB		<b>0</b> 1GB
nternal Datalogging Datalog Records ABD0100.1.8 Mode nternal Memory darmonics dinimum Window Size Dimensions - Excl. Feet 1 x W x D (mm)	16000  192kB 50	16000 — 192kB 50	 200МВ 100	0 1GB 417

All specifications at 23°C ± 5°C. These specifications are quoted in good faith but Newtons4th Ltd reserves the right to amend any specification at any time without notice

The N4L product range also includes Frequency Response and Impedance Analyzers, Selective Level Meters and Laboratory Power



## Applications



- Power supply phase margin and gain margin (FRA)
- Inductance, Capacitance and Resistance (LCR)
- Analysis of mechanical vibration (HARM)
- Phase Angle Voltmeter (PAV)

Contact your local N4L Distributor for further details

## Newtons4th

Newtons4th Ltd (abbreviated to N4L) was established in 1997 to design, manufacture and support innovative electronic equipment to a world-wide market, specialising in sophisticated test equipment particularly related to phase measurement. The company was founded on the principle of using the latest technology and sophisticated analysis techniques in order to provide our customers with accurate, easy to use instruments at a lower price than has been traditionally associated with these types of measurements. Flexibility in our products and an attitude to providing the solutions that our customers really want has allowed us to develop many innovative functions in our ever increasing product range.



Newtons4th Ltd are ISO9001 registered, the internationally recognised standard for the quality management of husinesses



In recognition of the technical innovation and commercial success of the PPA series, N4L received the "Innovation 2010" Queen's award for enterprise

Distributed by:



nbn Elektronik AG **Birmensdorferstrasse 30** CH-8142 Uitikon

Tel. +41 (0)44 404 34 34 Fax +41 (0)44 493 50 32 sales@nbn-elektronik.ch Newtons4th Ltd 30 Loughborough Road Mountsorrel Loughborough LE12 7AT UK Phone: +44 (0)116 230 1066 +44 (0)116 230 1061 Fax: Email: sales@newtons4th.com Web: www.newtons4th.com