

Clamp-on Testers

CL Series and 30031 of Clamp-on Testers

Our CL Series offers wide range of current measurement

- AC Current Measurement CL120/130/135/150/155
- AC/DC Current Measurement CL220/235/250/255
- Leakage Current Measurement CL320/340/345/360



Yokogawa M&C Corporation

Selection Guide

■ For AC Current

Model		CL120	CL130	CL135	CL150	CL155	Notes
Diameter of measurable conductor		∅24mm	∅30mm	∅30mm	∅54mm	∅54mm	
Display		1999	1999	1999	3999	3999	
DC current	Range	—	—	—	—	—	
	Resolution	—	—	—	—	—	
AC current	Range	20/200A	200/600A	200/600A	400/2000A	400/2000A	
	Resolution	0.01A	0.1A	0.1A	0.1A	0.1A	
	Frequency characteristics	40~1kHz	40~1kHz	40~1kHz	40~1kHz	40~1kHz	
	Method of detection	Mean value	Mean value	True RMS	Mean value	True RMS	
Other measurement	AC voltage	—	○	○	○	○	
	DC voltage	—	—	—	○	○	
	Continuity check	—	○	○	○	○	
	Frequency	—	—	—	—	—	
	Temperature	—	—	—	—	—	
Other functions	Recorder output	—	—	—	○	○	
	Waveform monitor output	—	—	—	—	—	
	Data hold	○	○	○	○	○	
	Auto hold	—	—	—	—	—	
	Peak hold	—	—	—	○	○	
	maximum value memory	—	—	—	—	—	
	Mean value display	—	—	—	—	—	
	Filter	—	—	—	—	—	
	Range hold (current range)	○	○	○	○(current range)	○(current range)	
	Auto ZERO adjust	—	—	—	—	—	
	Auto power-off	○	—	—	—	—	.Sleep function (power-down)
	Page		1	1	2	2	3

■ For AC/DC Currents

Model		CL220	CL235	CL250	CL255	Notes
Diameter of measurable conductor		∅24mm	∅33mm	∅55mm	∅55mm	
Display		3999	3999	3999	3999	
DC current	Range	40/300A	400/1000A	400/2000A	400/2000A	
	Resolution	0.01A	0.1A	0.1A	0.1A	
AC current	Range	40/300A	400/600A	400/2000A	400/2000A	
	Resolution	0.01A	0.1A	0.1A	0.1A	
	Frequency characteristics	20~1kHz	40~1kHz	40~1kHz	30~1kHz	
	Method of detection	Mean value	True RMS	Mean value	True RMS	
Other measurement	AC voltage	—	○	○	○	
	DC voltage	—	○	○	○	
	Continuity check	—	○	○	○	
	Frequency	—	○	—	○	
	Temperature	—	—	—	—	
Other functions	Recorder output	—	—	○	○	
	Waveform monitor output	—	—	—	—	
	Data hold	○	○	○	○	
	Auto hold	—	—	—	—	
	Peak hold	—	○	—	○	
	maximum value memory	—	—	○	—	
	Mean value display	—	○	—	○	
	Filter	—	—	—	—	
	Range hold (current range)	—	—	○(current range)	—	
	Auto ZERO adjust	○	○	○	○	
	Auto power-off	—	—	—	—	.Sleep function (power-down)
	Page		4	4	5	5

■ For Leakage Current

Model		CL320	CL340	CL345	CL360	30031	Notes
Diameter of measurable conductor		∅24mm	∅40mm	∅40mm	∅68mm	∅40mm	
Display		1999	3999	4200	1999	3200	
DC current	Range	—	—	—	—	—	
	Resolution	—	—	—	—	—	
AC current	Range	20/200mA,200A	40/400mA,400A	40/400mA,400A	200mA/2/20/200/1000A	3/30mA 30/60A	
	Resolution	0.01mA	0.01mA	0.01mA	0.1mA	0.001mA	
	Frequency characteristics	40~400Hz	20~1kHz	20~1kHz	40~1kHz	50/60Hz	
	Method of detection	Mean value	Mean value	True RMS	Mean value	Mean value	
Other measurement	AC voltage	—	—	—	—	—	
	DC voltage	—	—	—	—	—	
	Continuity check	—	—	—	—	—	
	Frequency	—	—	—	—	—	
	Temperature	—	—	—	—	—	
Other functions	Recorder output	—	—	—	○	—	
	Waveform monitor output	—	—	—	○	—	
	Data hold	○	○	○	○	○	
	Auto hold	—	—	—	—	—	
	Peak hold	—	○	○	○	—	
	maximum value memory	—	—	—	—	—	
	Mean value display	—	—	—	—	—	
	Filter	○	○	○	○	—	
	Range hold (current range)	○	○	○	○	—	
	Auto ZERO adjust	—	—	—	—	—	
	Auto power-off	○	○	○	—	○	
	Page		6	6	7	7	8

Clamp-on Testers

CL120



AC A

∅ 24

AC/20~200A

CL130



AC A

∅ 30

AC/200~600A

AC V/Ω

CL120

Light weight & compact design
 Mean value display
 Data hold function
 Approved for conformity to safety standards EN61010-1,
 EN61010-2-032 (CAT. III 300 V)

Specifications

Accuracy: \pm (% rdg + dgt) = \pm (% readout + value of least significant digit)
 At 23 ±5 75%RH or less

Parameter	Reference	Accuracy
AC current	20A	2.0+7 (50 ~ 1kHz)
	200A	2.0+5 (50/60Hz) 3.0+10 (40 ~ 1kHz)

General Specifications

Parameter	Specification
Method of detection	Mean value
Display	LCD(Digital display:1999 counts)
Response time	Approx. 2 seconds
Range switching	Manual-range
Data hold	On all range
Ambient temperature and humidity	0-40 , 85% RH or less (no condensation)
Temperature coefficient	-
Influence of external magnetic field	0.8A or less at 400A/m
Influence of conductor position	±2% or less
Safety standard	Conforms EN 61010-1, EN61010-2-032
Circuit voltage	300Vrms or less
Withstanding voltage	3.7kV AC for one minute
Power supply	LR-44 ×2(3V) or SR-44 ×2
Battery life	Approx. 100 hours (continuous)
Consumed current	Approx. 1mA
Auto power-off	Approx. 10 minutes
Diameter of measurable conductor	24mm at maximum
Dimensions	Approx. 59(W)×148(H)×26(D)mm
Weight	Approx. 100g
Accessories	User's manual(IM CL120), batteries, carrying case(93033)

CL130

Mean value display
 Data hold function
 Approved for conformity to safety standards EN61010-1,
 EN61010-2-031, EN61010-2-032 (CAT. III 600 V)

Specifications

Accuracy: \pm (% rdg + dgt) = \pm (% readout + value of least significant digit)
 At 23 ±5 75%RH or less

Parameter	Reference	Accuracy
AC current	200A	1.5+6 (50/60Hz)
		2.0+5 (40 ~ 1kHz)
	600A	1.0+3 (50/60Hz) 2.0+5 (40 ~ 1kHz)
AC voltage	200V/600V	1.0+2 (50/60Hz)
		1.5+4 (40 ~ 1kHz)
Resistance	200	1.2+4 , Beeps at below 30 (continuity check)

General Specifications

Parameter	Specification
Method of detection	Mean value
Display	LCD(Digital display:1999 counts)
Response time	Approx. 1 second (approx. 2 seconds on resistance range)
Range switching	Manual-range
Data hold	On all range
Ambient temperature and humidity	-10-50 , (no condensation) up to 30 , 90% RH up to 40 , 75% RH up to 50 , 45% RH
Temperature coefficient	-
Influence of external magnetic field	2A or less at 400A/m
Influence of conductor position	±2% or less
Safety standard	Conforms EN 61010-1, EN61010-2-031, EN61010-2-032
Circuit voltage	600Vrms or less
Withstanding voltage	5.55kV AC for one minute
Power supply	6F22(006P)9V ×1 or 6LR61 ×2
Battery life	Approx. 200 hours (continuous)
Consumed current	Approx. 2mA
Auto power-off	Approx. 10 minutes
Diameter of measurable conductor	30mm at maximum
Dimensions	Approx. 93(W)×210(H)×40(D)mm
Weight	Approx. 400g
Accessories	User's manual(IM CL130), batteries, carrying case(93032)

Clamp-on Testers



- AC A
- ∅30
- AC/200~600A
- RMS
- AC V/Ω



- AC A
- ∅54
- AC/400~2000A
- AC V/DC V/Ω

CL135

True RMS Display
Data hold function
Approved for conformity to safety standard EN61010-1,
EN61010-2-031, EN61010-2-032 (CAT. III 600 V)

Specifications

At 23 ±5 75%RH or less
Accuracy: ± (% rdg + dgt) = ± (% readout + value of least significant digit)

Parameter	Reference	Accuracy
AC current	200A	1.5+4 (50/60Hz)
		2.0+5 (40 ~ 1kHz)
	600A	1.5+4 (50/60Hz)
		2.0+5 (40 ~ 1kHz)
AC voltage	200V/600V	1.0+2 (50/60Hz)
		1.5+4 (40 ~ 1kHz)
		3 (50/60Hz)
Crest factor	40A	3 (50/60Hz)
Resistance	200	1.2+4, Beeps at below 30 (continuity check)

General Specifications

Parameter	Specification
Method of detection	True RMS
Display	LCD(Digital display:1999 counts)
Response time	Approx. 1 second (approx. 2 seconds on resistance range)
Range switching	Manual-range
Data hold	On all range
Ambient temperature and humidity	-10-50 , (no condensation)
	up to 30 , 90%RH
	up to 40 , 75%RH
	up to 50 , 45%RH
Temperature coefficient	-
Influence of external magnetic field	2A or less at 400A/m
Influence of conductor position	± 3% or less
Safety standard	Conforms EN61010-1, EN61010-2-031, EN61010-2-032
Circuit voltage	600Vrms or less
Withstanding voltage	5.55kV AC for one minute
Power supply	6F22(006P)9V × 1 or 6LR61 × 2
Battery life	Approx. 200 hours (continuous)
Consumed current	Approx. 2mA
Auto power-off	Approx. 10 minutes
Diameter of measurable conductor	30mm at maximum
Dimensions	Approx. 93(W)×210(H)×40(D)mm
Weight	Approx. 400g
Accessories	User's manual(IM CL130), batteries, carrying case(93032)

CL150

Mean value display
DC output function
Data hold function
Sleep function
Approved for conformity to safety standards EN61010-1,
EN61010-2-031, EN61010-2-032 (CAT. III 600 V, CAT. II 1000 V)

Specifications

At 23 ±5 75%RH or less
Accuracy: ± (% rdg + dgt) = ± (% readout + value of least significant digit)

Parameter	Reference	Accuracy
AC current	400A	1.0+3 (50/60Hz)
		2.0+3 (40 ~ 1kHz)
	2000A(0 ~ 1500A)	1.0+3 (50/60Hz)
		3.0+3 (40 ~ 1kHz)
AC voltage	2000A(1500 ~ 2000A)	3.0(50/60Hz)
		1.0+2 (50/60Hz)
		1.5+3 (40 ~ 1kHz)
DC voltage	40/400/1000V	1.0+2
Resistance	400/4k/40k/400k	1.5+2, Beeps at below 50±35 (continuity check)
DC output	400A(0 ~ 400mV)	± 1.5% rdg ± 0.5mV (50/60Hz)
		± 2.5% rdg ± 0.5mV (40 ~ 1kHz)
	2000A(0 ~ 150mV/0 ~ 1500A)	± 1.5% rdg ± 0.5mV (50/60Hz)
		± 3.5% rdg ± 0.5mV (40 ~ 1kHz)
2000A(150 ~ 200mV/1500 ~ 2000A)	± 3.5% rdg (50/60Hz)	

General Specifications

Parameter	Specification
Method of detection	Mean value
Display	LCD(Digital display:3999 counts)
Response time	Approx. 2 seconds
Range switching	Manual-range(on AC current range)/ Auto-range(on AC voltage range, resistance range)
Data hold	On all range
Peak hold	On AC current range
Ambient temperature and humidity	0-40 , 85% RH or less (no condensation)
Temperature coefficient	-
Influence of external magnetic field	1A or less at 400A/m
Influence of conductor position	± (2.0% rdg + 3dgt) or less
Safety standard	Conforms EN61010-1, EN61010-2-031, EN61010-2-032
Circuit voltage	1000Vrms or less
Withstanding voltage	5.55kV AC for one minute
Power supply	R6P(SUM-3) × 2 or LR6 × 2
Battery life	Approx. 150 hours (continuous)
Consumed current	Approx. 5mA
Sleep function	Automatically powered down in about 10 minutes after the last switch operation
Diameter of measurable conductor	54mm at maximum
Dimensions	Approx. 105(W)×247(H)×49(D)mm
Weight	Approx. 470g
Accessories	User's manual(IM CL150), batteries, carrying case(93034)

Clamp-on Testers

CL155



- AC A
- ∅54
- AC/400~2000A
- RMS
- AC V/DC V/Ω

CL155

- True RMS display
- DC output function
- Data hold function
- Sleep function

Approved for conformity to safety standards EN61010-1, EN61010-2-031, EN61010-2-032 (CAT. III 600 V, CAT. II 1000 V)

Specifications

At 23 ± 5 75%RH or less
Accuracy: ± (% rdg + dgt) = ± (% readout + value of least significant digit)

Parameter	Reference	Accuracy
AC current	400A	1.0+3 (50/60Hz)
		2.0+3 (40 ~ 1kHz)
	2000A(0 ~ 1500A)	1.0+3 (50/60Hz)
		3.0+3 (40 ~ 1kHz)
2000A(1500 ~ 2000A)	3.0(50/60Hz)	
AC voltage	40/400/750V	1.0+2 (50/60Hz)
		1.5+3 (40 ~ 1kHz)
DC voltage	40/400/1000V	1.0+2
Resistance	400/4k/40k/400k	1.5+2, Beeps at below 50±35 (continuity check)
DC output	400A(0 ~ 400mV)	± 1.5% rdg ± 0.5mV (50/60Hz)
		± 2.5% rdg ± 0.5mV (40 ~ 1kHz)
	2000A(0 ~ 150mV/0 ~ 1500A)	± 1.5% rdg ± 0.5mV (50/60Hz)
		± 3.5% rdg ± 0.5mV (40 ~ 1kHz)
2000A(150 ~ 200mV/1500 ~ 2000A)	± 3.5% rdg (50/60Hz)	

General Specifications

Parameter	Specification
Method of detection	True RMS
Display	LCD(Digital display:3999 counts)
Response time	Approx. 2 seconds
Range switching	Manual-range(on AC current range)/ Auto-range(on AC voltage range, resistance range)
Data hold	On all range
Peak hold	On AC current range
Ambient temperature and humidity	0-40 , 85% RH or less (no condensation)
Temperature coefficient	—
Influence of external magnetic field	1A or less at 400A/m
Influence of conductor position	±(2.0% rdg + 3dgt) or less
Safety standard	Conforms EN61010-1, EN61010-2-031, EN61010-2-032
Circuit voltage	1000Vrms or less
Withstanding voltage	5.55kV AC for one minute
Power supply	R6P(SUM-3) ×2 or LR6 ×2
Battery life	Approx. 150 hours (continuous)
Consumed current	Approx. 5mA
Sleep function	Automatically powered down in about 10 minutes after the last switch operation
Diameter of measurable conductor	54mm at maximum
Dimensions	Approx. 105(W)×247(H)×49(D)mm
Weight	Approx. 470g
Accessories	User's manual(IM CL150), batteries, carrying case(93034)

Clamp-on Testers

CL220



AC A/DC A

∅ 24

AC/40~300A

DC/40~300A

CL235



AC A/DC A

∅ 33

AC/400~600A

RMS

DC/400~1000A

DC V/AC V/
Ω /Hz

CL220

Light weight & compact design
Mean value display
Sleep function
Approved for conformity to safety standards EN61010-1, EN61010-2-032 (CAT. III 300 V)

Specifications

At 23 ±5 75%RH or less
Accuracy: ±(% rdg + dgt) = ±(% readout + value of least significant digit)

Parameter	Reference	Accuracy
DC current	40A	1.0+4
	300A(±20 ~ ±200A)	1.5+4
	300A(±200 ~ ±300A)	3.0
AC current	40A	1.0+4 (50/60Hz)
		2.5+4 (20 ~ 1kHz)
		1.5+4 (50/60Hz)
	300A(20 ~ 200A)	2.5+4 (20 ~ 1kHz)
		3.5 (50/60Hz)
	300A(200 ~ 300A)	4.0 (20 ~ 1kHz)

General Specifications

Parameter	Specification
Method of detection	Mean value
Display	LCD(Digital display:3999 counts)
Response time	Approx. 2 seconds
Range switching	Auto-range
Data hold	On all range
Ambient temperature and humidity	0-40 , 85% RH or less (no condensation)
Temperature coefficient	-
Influence of external magnetic field	1A or less at 400A/m
Influence of conductor position	±(2.0% rdg + 5dgt) or less
Safety standard	Conforms EN61010-1, EN61010-2-032
Circuit voltage	300Vrms or less
Withstanding voltage	3.7kV AC for one minute
Power supply	LR-44 ×2(3V) or SR-44 ×2
Battery life	Approx. 11 hours (continuous)
Consumed current	Approx. 9mA
Sleep function	Automatically powered down in about 5 minutes after the last switch operation
Diameter of measurable conductor	24mm at maximum
Dimensions	Approx. 59(W)×147(H)×25(D)mm
Weight	Approx. 100g
Accessories	User's manual(IM CL220), batteries, carrying case(93033)

CL235

True RMS display
Sleep function
Data hold function
Approved for conformity to safety standards EN61010-1, EN61010-2-031, EN61010-2-032 (CAT. III 600 V)

Specifications

At 23 ±5 75%RH or less
Accuracy: ±(% rdg + dgt) = ±(% readout + value of least significant digit)

Parameter	Reference	Accuracy
AC current	400/600A	1.5+5 (50/60Hz)
		3.5+5 (40 ~ 1kHz)
DC current	400/1000A	1.0+5
AC voltage	40/400/600V	1.5+5 (50/60Hz)
		3.5+5 (40 ~ 1kHz)
DC voltage	40/400/600V	1.0+5
Crest factor		3
Resistance	400/4000	1.0+5 , Beeps at below 20 (continuity check)
Frequency	10 ~ 3000Hz	1.5+5

General Specifications

Parameter	Specification
Method of detection	True RMS
Display	LCD(Digital display:3999 counts)
Response time	Approx. 2 second
Range switching	Auto-range
Data hold	On all range
Peak hold	On AC/DC current range, AC/DC voltage range
Average measurement	-
Ambient temperature and humidity	0-40 , 90% RH or less (no condensation)
Temperature coefficient	-
Influence of external magnetic field	-
Influence of conductor position	±2% or less
Safety standard	Conforms EN61010-1, EN61010-2-031, EN61010-2-032
Circuit voltage	600Vrms or less
Withstanding voltage	5.55kV AC for one minute
Power supply	6F22(006P)9V ×1 or 6LR61 ×1
Battery life	Approx. 15 hours (continuous)
Consumed current	Approx. 15mA
Sleep function	Automatically powered down in about 30 minutes after the last switch operation
Diameter of measurable conductor	33mm at maximum
Dimensions	Approx. 91(W)×210(H)×40(D)mm
Weight	Approx. 450g
Accessories	User's manual(IM CL235), batteries, carrying case(93032)

Clamp-on Testers

CL250



AC A/DC A

∅55

AC/400~2000A

DC/400~2000A

AC V/DC V/Ω

CL250

Mean value display
Sleep function
Data hold function
Approved for conformity to safety standards EN61010-1, EN61010-2-031, EN61010-2-032 (CAT. III 600 V, CAT. II 1000 V)

Specifications

At 23 ±5 75%RH or less
Accuracy: ± (% rdg + dgt) = ± (% readout + value of least significant digit)

Parameter	Reference	Accuracy
DC current	400/2000A	1.5+2
AC current	400A/2000A(0 ~ 1000A)	1.5+2 (50/60Hz)
		3.0+4 (40 ~ 500Hz)
		5.0+4 (500 ~ 1kHz)
	2000A(1001 ~ 2000A)	3.0+2 (50/60Hz)
DC voltage	400/1000V	1.0+2
AC voltage	400/750V	1.5+2 (50/60Hz)
		1.5+4 (40 ~ 1kHz)
Resistance	400/4000	1.5+2, Beeps at below 50±35 (continuity check)
DC output	DC400A(0 ~ 400mV)	± 1.5% rdg ± 3mV
	DC2000A(0 ~ 200mV)	± 1.5% rdg ± 3mV
	AC400A(0 ~ 400mV)	± 1.5% rdg ± 3mV (50/60Hz)
	AC2000A(0 ~ 100mV/0 ~ 1000A)	± 3.0% rdg ± 3mV (40 ~ 500Hz)
	AC2000A(100.1 ~ 200mV/1001 ~ 2000A)	± 5.0% rdg ± 3mV (500 ~ 1kHz)

General Specifications

Parameter	Specification
Method of detection	Mean value
Display	LCD(Digital display:3999 counts)
Response time	Approx. 2 seconds
Range switching	Manual-range(on current, voltage range) /Auto-range(on resistance range)
Peak hold	On all range
Max hold	On current/voltage range
Ambient temperature and humidity	0-40 , 85% RH or less (no condensation)
Temperature coefficient	-
Influence of external magnetic field	4A or less at 400A/m
Influence of conductor position	±(1.5% rdg + 3dgt) or less
Safety standard	Conforms EN61010-1, EN61010-2-031, EN61010-2-032
Circuit voltage	1000Vrms or less
Withstanding voltage	5.55kV AC for one minute
Power supply	R6P(SUM-3) ×2 or LR6 ×2
Battery life	Approx. 100 hours (continuous)
Consumed current	Approx. 9mA
Sleep function	Automatically powered down in about 10 minutes after the last switch operation
Diameter of measurable conductor	55mm at maximum
Dimensions	Approx. 105(W)×250(H)×49(D)mm
Weight	Approx. 530g
Accessories	User's manual(IM CL250), Test Lead(98011), Output plug(98012), batteries, carrying case(93034)

CL255



AC A/DC A

∅55

AC/400~2000A

DC/400~2000A

RMS

AC V/DC V/Ω/Hz

CL255

True RMS display
Sleep function
Data hold function
Approved for conformity to safety standards EN61010-1, EN61010-2-031, EN61010-2-032 (CAT. III 600 V, CAT. II 1000 V)

Specifications

At 23 ±5 75%RH or less
Accuracy: ± (% rdg + dgt) = ± (% readout + value of least significant digit)

Parameter	Reference	Accuracy
DC current	400/2000A	1.5+2
AC current	400A/2000A(150 ~ 1700A)	1.5+3 (50/60Hz) 3.0+4 (30 ~ 1kHz)
	2000A(1701 ~ 2000A)	3.5+3 (50/60Hz)
DC voltage	40/400/1000V	1.0+2
AC voltage	40/400/750V	1.5+3 (50/60Hz)
		2.0+4 (30 ~ 1kHz)
Crest factor		3
Resistance	400/4000	1.5+2, Beeps at below 20 (continuity check)
Frequency	10 ~ 3999Hz	1.5+5
DC output	DC400A(0 ~ 400mV)	± 1.5% rdg ± 3mV
	DC2000A(15 ~ 200mV)	± 1.5% rdg ± 3mV
	AC400A(0 ~ 400mV)	± 1.5% rdg ± 3mV (50/60Hz)
	/AC2000A(15 ~ 170mV/150 ~ 1700A)	± 3.0% rdg ± 3mV (40 ~ 1kHz)
	AC2000A(170.1 ~ 200mV/1701 ~ 2000A)	± 3.5% rdg ± 3mV (50/60Hz)

General Specifications

Parameter	Specification
Method of detection	True RMS
Display	LCD(Digital display:3999 counts)
Response time	Approx. 1 second(on DC current/voltage range), Approx. 2 seconds(AC current/voltage range, resistance range)
Range switching	Auto-range
Data hold	On all range (without peak hold)
Peak hold	On current/voltage range
Average Measurement	On current/voltage range
Ambient temperature and humidity	0-40 , 85% RH or less (no condensation)
Temperature coefficient	-
Influence of external magnetic field	4A or less at 400A/m
Influence of conductor position	±(1.5% rdg + 3dgt) or less
Safety standard	Conforms EN61010-1, EN61010-2-031, EN61010-2-032
Circuit voltage	1000Vrms or less
Withstanding voltage	5.55kV AC for one minute
Power supply	6F22(006P)9V ×1 or 6LR61 ×1
Battery life	Approx. 15 hours (continuous)
Consumed current	Approx. 15mA
Sleep function	Automatically powered down in about 10 minutes after the last switch operation
Diameter of measurable conductor	55mm at maximum
Dimensions	Approx. 105(W)×250(H)×49(D)mm
Weight	Approx. 540g
Accessories	User's manual(IM CL255), Test Lead(98011), Output plug(98012), batteries, carrying case(93034)

Leakage Clamp-on Testers

CL320



AC Leak

∅ 24

AC/20mA~200A

CL340



AC Leak

∅ 40

AC/40mA~400A

CL320

Mean value display
Auto power-off
Manual range switching
Approved for conformity to safety standards EN61010-1, EN61010-2-032(CAT. III 300 V)

Specifications

At 23 ±5 75%RH or less
Accuracy: ±(% rdg + dgt) = ±(% readout + value of least significant digit)

Parameter	Reference	Accuracy	
		WIDE(40 ~ 400Hz)	50/60Hz
AC current	20mA/200mA	2.0+4 (50/60Hz)	3.0+5 (50/60Hz)
	200A(0 ~ 100A)	5.0+6 (40 ~ 400Hz)	
	200A(100.1 ~ 200A)	5.0+4 (50/60Hz)	5.0+5 (50/60Hz)

General Specifications

Parameter	Specification
Method of detection	Mean value
Display	LCD(Digital display:1999 counts)
Response time	Approx. 2 seconds
Range switching	Manual-range
Data hold	On all range
Ambient temperature and humidity	0-40 , 85% RH or less (no condensation)
Temperature coefficient	—
Influence of external magnetic field	10mA or less in proximity to a 14.4mm-dia conductor carrying 100A
Influence of conductor position	Within 5dgt for 0 to 50A, or 2% for 50 to 200A (10mm-dia conductor at inside the jaw)
Influence of residual current	10mA or less in proximity to a 10mm-dia conductor carrying 50A
Safety standard	Conforms EN61010-1, EN61010-2-032
Circuit voltage	300Vrms or less
Withstanding voltage	3.7kV AC for one minute
Power supply	LR-44 ×2(3V) or SR-44 ×2
Battery life	Approx. 15 hours (continuous)
Consumed current	Approx. 5mA
Auto power-off	Approx. 10 minutes
Diameter of measurable conductor	24mm at maximum
Dimensions	Approx. 60(W)×149(H)×26(D)mm
Weight	Approx. 120g
Accessories	User's manual(IM CL320), batteries, carrying case(93033)

CL340

Mean value display
Auto power-off
Manual range switching
Approved for conformity to safety standards EN61010-1, EN61010-2-032 (CAT. III 300 V)

Specifications

At 23 ±5 75%RH or less
Accuracy: ±(% rdg + dgt) = ±(% readout + value of least significant digit)

Parameter	Reference	Accuracy	
		WIDE(20Hz ~)	50/60Hz
AC current	40mA/400mA	2.5+10 (20 ~ 1kHz)	1.0+5 (50/60Hz)
	400A(0 ~ 350A)	2.5+10 (40 ~ 1kHz)	1.0+5 (50/60Hz)
	400A(350 ~ 400A)	5.0 (40 ~ 1kHz)	2.0 (50/60Hz)

General Specifications

Parameter	Specification
Method of detection	Mean value
Display	LCD(Digital display:3999 counts)
Response time	Approx. 2 seconds
Range switching	Manual-range
Data hold	On all range
Peak hold	On all range
Ambient temperature and humidity	0-40 , 85% RH or less (no condensation)
Temperature coefficient	—
Influence of external magnetic field	10mA or less in proximity to a 15mm-dia conductor carrying 100A
Influence of conductor position	40/400mA range: Within 5dgt at every part inside the jaw 400A range: Within ±0.5%rdg ±5dgt at every part inside the jaw section
Influence of residual current	12mA or less in proximity to a 10mm-dia conductor carrying 100A
Safety standard	Conforms EN61010-1, EN61010-2-032
Circuit voltage	300Vrms or less
Withstanding voltage	3.7kV AC for one minute
Power supply	R0-3(UM-4) × 2 or LR03 × 2
Battery life	Approx. 40 hours (continuous)
Consumed current	Approx. 13mA
Auto power-off	Approx. 10 minutes
Diameter of measurable conductor	40mm at maximum
Dimensions	Approx. 81(W)×185(H)×40(D)mm
Weight	Approx. 270g
Accessories	User's manual(IM CL340), batteries, carrying case(93030)

Leakage Clamp-on Testers

CL345



AC Leak

∅ 40

AC/40mA~400A

RMS

CL345

True RMS display
Auto power-off
Manual range switching
Approved for conformity to safety standards EN61010-1,
EN61010-2-032 (CAT. III 300 V)

Specifications

At 23 ±5 75%RH or less
Accuracy: ± (% rdg + dgt) = ± (% readout + value of least significant digit)

Parameter	Reference	Accuracy	
		WIDE(20Hz ~)	50/60Hz
AC current	40mA/400mA	2.5+10 (20 ~ 1kHz)	1.0+5 (50/60Hz)
	400A(0 ~ 300A)	2.5+10 (40 ~ 1kHz)	1.0+5 (50/60Hz)
	400A(300 ~ 400A)	5.0 (40 ~ 1kHz)	2.0 (50/60Hz)

General Specifications

Parameter	Specification
Method of detection	True RMS
Display	LCD(Digital display:4200 counts)
Response time	Approx. 2 seconds
Range switching	Manual-range
Data hold	On all range
Peak hold	On all range
Ambient temperature and humidity	0-40 , 85% RH or less (no condensation)
Temperature coefficient	-
Influence of external magnetic field	10mA or less in proximity to a 15mm-dia conductor carrying 100A
Influence of conductor position	40/400mA range: Within 5dgt at every part inside the jaw 400A range: Within ±0.5%rdg ±5dgt at every part inside the jaw section
Influence of residual current	12mA or less in proximity to a 10mm-dia conductor carrying 100A
Safety standard	Conforms EN61010-1, EN61010-2-032
Circuit voltage	300Vrms or less
Withstanding voltage	3.7kV AC for one minute
Power supply	R0-3(UM-4) × 2 or LR03 × 2
Battery life	Approx. 24 hours (continuous)
Consumed current	Approx. 21mA
Auto power-off	Approx. 10 minutes
Diameter of measurable conductor	40mm at maximum
Dimensions	Approx. 81(W)×185(H)×32(D)mm
Weight	Approx. 270g
Accessories	User's manual(IM CL340), batteries, carrying case(93030)

CL360



AC Leak

∅ 68

AC/200mA~1000A

CL360

Approved for conformity to safety standards EN 61010-1,
EN 61010-2-032 (CAT III 300 V)

Specifications

At 23 ±5 75%RH or less
Accuracy: ± (% rdg + dgt) = ± (% readout + value of least significant digit)

Parameter	Reference	Accuracy	
		WIDE(40 ~ 1kHz)	50/60Hz
AC current	200mA/2A/20A	1.0+2 (50/60Hz)	1.5+2
		3.0+2 (40 ~ 1kHz)	
	200A	1.5+2 (50/60Hz)	2.0+2
		3.5+2 (40 ~ 1kHz)	
1000A(0 ~ 500A)	1.5+2 (50/60Hz)	2.0+2	
	3.5+2 (40 ~ 1kHz)		
1000A(501 ~ 1000A)	5.0 (50/60Hz)	5.5	
	10.0 (40 ~ 1kHz)		
AC output	200mA/2A/20A(0 ~ 200mV)	2.0	2.0
	200A(0 ~ 200mV)	2.5	2.5
	1000A(0 ~ 50mV/0 ~ 500A)	3.0	3.0
	1000A/(50 ~ 100mV/501 ~ 1000A)	5.0	5.0
DC output	200mA/2A/20A(0 ~ 200mV)	3.0	3.5
	200A(0 ~ 200mV)	3.5	4.0
	1000A(0 ~ 50mV/0 ~ 500A)	5.0	5.5
	1000A/(50 ~ 100mV/501 ~ 1000A)	7.0	7.5

General Specifications

Parameter	Specification
Method of detection	Mean value
Display	LCD(Digital display:1999 counts)
Response time	Approx. 1 second
Range switching	Manual-range
Data hold	On all range
Peak hold	On all range
Ambient temperature and humidity	-10-50 , 80% RH or less (no condensation)
Temperature coefficient	-
Influence of external magnetic field	15mA or less in proximity to a 10mm-dia conductor carrying 100A
Influence of conductor position	2% or less
Influence of residual current	10mA or less in proximity to a 10mm-dia conductor carrying 100A
Safety standard	Conforms EN61010-1, EN61010-2-032
Circuit voltage	300Vrms or less
Withstanding voltage	3.7kV AC for one minute
Power supply	6F22(006P)9V × 1 or 6LR61 × 1
Battery life	Approx. 60 hours (continuous)
Consumed current	Approx. 5mA
Diameter of measurable conductor	68mm at maximum
Dimensions	Approx. 129(W)×248(H)×55(D)mm
Weight	Approx. 570g
Accessories	User's manual(IM CL360), batteries, carrying case(93031)

Leakage Clamp-on Testers

30031



Compact

AC A
50/60Hz

3mA~60A

∅40

AC Leakage

30031

Can measure leakage currents of 1 mA, which is useful for checking the insulation of low-voltage circuits and electrical components.

Can measure a broad range of currents from leakage currents (at a resolution of 0.001 mA) to load currents up to 60 A.

Typical influence (on the current value of an adjacent cable) from an external magnetic field is 0.0005%.

Durability of clamp: More than 50,000 opening/closing events

Twice the torsional strength of Yokogawa M&C's earlier model clamps

The clamp lever is lengthened by 30%, enabling smooth opening/closing of the clamp even for thick cables of 40mm in diameter.

Approved for conformity to safety standards EN 61010-1 and EN 61010-2-032 (CAT III 300V, pollution degree2)

Specifications

At 23 ±5 80%RH or less
Accuracy: ±(% rdg + dgt) = ±(% readout + value of least significant digit)

AC current	3/30mA,30/60A
Frequency characteristics	50/60Hz
Accuracy*	1.0 + 5 (0~30mA) 1.0 + 5 (0~50A) 5.0 + 5 (50~60A)

General Specifications

Method of detection	Mean value
Display	LCD (Digital display: 3200 counts) (Bar-graph display: 32 segments)
Measurement cycle	2 times/second (Digital display), 12 times/second (Bar-graph display)
Range switching	Auto-range
Ambient temperature and humidity	0 - 50 , 80% RH or less (no condensation)
Temperature coefficient	0.05% of range/ or less (within the ranges of 0-18 and 28-50 for measurement of 0-50 A)
Influence of external magnetic field	0.0005% typical*1 (on current value of adjacent cable)
Influence of conductor position	Within accuracy
Circuit voltage	300 Vrms or less
Safety standard	Approved for conformity to EN 61010-1,EN 61010-2-032
Withstanding voltage	3.7 kV AC for one minute
Power supply	One CR2032 (Coin-shaped) 3 V battery
Battery life	Approx. 90 hours (when continuously used)
Auto power-off	Approx. 10 minutes
Diameter of measurable conductor	40 mm at maximum
Dimensions	Approx. 70(W)×176(H)×25(D) excluding protrusions
Weight	Approx. 200 g
Accessories	Instruction manual, battery, soft case

Clamp-on Testers

96001



20Hz~20kHz

AC A

∅33

96001

Compact and light with high-performance

20Hz to 20kHz wide frequency characteristics

Can be connected to a digital multimeter

Need not be connected to a power source

Fit to waveform measurement using oscilloscopes and oscillographic recorders

Specifications

Measuring range	0 to 400 A ACrms (600 A peak)	
Output voltage	0 to 4 V ACrms (10mV/A)	
Accuracy (at 23 ±5 , sine wave input)	(amplitude)	±1.5% of rdg ±0.4mV (20Hz to 40Hz) ±1.0% of rdg ±0.2mV (40Hz to 1kHz) ±(0.8+0.2 × f kHz)% of rdg ±(0.2+0.04 × f kHz)mV (1 to 20kHz)
	(phase)	Within ±3.0 (40Hz to 1kHz)
	Temperature coefficient	0.05% fs/ in a range of 0 to 18 and 28 to 50
Output impedance	Approximately 30	
Load impedance	100k min./100 pF max.	
Effect of external magnetic field	2mV(0.2A)or less at 400A/m	
Voltage of circuit under measurement	600V ACrms maximum	
Diameter of applicable conductor	Maximum diameter of 33 mm	
Operating temperature and humidity limits	0 to 50 , 80% R.H. max.(non-condensing)	
Storage temperature limits	-20 to 60 (non-condensing)	
Withstanding voltage	3.7kV AC for one minute (core and case, and core and output terminals)	
Safety	Conforms to IEC 1010.	
External dimensions	Approximately 70(W)×130(H)×30(D)mm	
Weight	Approximately 220g	
Output cord length	Approximately 2.5 meters(with banana plug)	
Accessories	One portable case and one instruction manual	

Accessories

■ Supplementary Products

Item	Model	Specification	Applicable model
Carrying case	RB057	Soft type	30031

■ 99025 Specifications

Item	Specifications
Measuring Range	0 ~ AC3000A
Ratio/Range	10:1 (input to output)
Accuracy	±2% of input ±0.5A
Allowable Measurement Time	0 ~ 1000A(continuous), 1000 ~ 1500A(10 minutes max.), 3000A(30 seconds max.)
Conductor Size	100mm max. (100×150mm)
Frequency Response	50Hz/60Hz
Safety Standard	EN61010-1 CAT.III300V Pollution Degree 2
Withstand Voltage	AC3700V for 1 minute
Dimensions	150(W)×317(H)×33(D)mm 40(W)×45(H)×10(D)mm Output coil
Weight	Approx. 750g
Accessories	93035(Carrying Case)
For use with following models	

Clamp Adapter : 99025



Output Cable for Terminal Screw : 91019



Output Cable with Banana Plug : 91020



■ Optional Accessories

Item	Model	Specification	Applicable model
Output Cable for Terminal Screw	91019	Cable length: approx.1.1m	CL150,CL155 CL250,CL255
Output Cable with Banana Plug	91020	Cable length: approx.2.0m	CL360
Clamp Adapter	99025	Ratio/Range = 10:1/3000A	CL120,CL130,CL135,CL150, CL155,CL220,CL235,CL250, CL255,CL320,CL340,CL345

■ Supplementary Products

Item	Model	Specification	Applicable model
Test Lead	98010	Angle Plug type	CL130,CL135,CL235
Test Lead	98011	Straight Plug type	CL150,CL155,CL250,CL255
Output Plug	98012	3pcs/set	CL150,CL155,CL250,CL255
Carrying Case	93030	Hard type	CL340,CL345
Carrying Case	93031	Soft type	CL360
Carrying Case	93032	Soft type	CL130,CL135,CL235
Carrying Case	93033	Soft type	CL120,CL220,CL320
Carrying Case	93034	Soft type	CL150,CL155,CL250,CL255
Carrying Case	93035	Hard type	99025

Test lead : 98010



Test lead : 98011



Output Plug : 98012



Carrying case : 93030



Carrying case : 93031



Carrying case : 93032



Carrying case : 93033



Carrying case : 93034



Carrying case : 93035



 **NOTICE**

- Before using the product, read the instruction manual carefully to ensure proper and safe operation.

YOKOGAWA M&C CORPORATION 2-9-32 Nakacho, Musashino-shi, Tokyo, 180-8750 Japan
International Sales Dept. Phone: +81-422-52-5716 Facsimile: +81-422-55-8954

Represented by:

YOKOGAWA CORPORATION OF AMERICA (U.S.A.)	Phone: +1-770-253-7000	Facsimile: +1-770-251-2088
YOKOGAWA EUROPE B. V. (THE NETHERLANDS)	Phone: +31-334-64-1611	Facsimile: +31-334-64-1610
YOKOGAWA ENGINEERING ASIA PTE. LTD. (SINGAPORE)	Phone: +65-6241-9933	Facsimile: +65-6241-2606
YOKOGAWA AMERICA DO SUL LTDA (BRAZIL)	Phone: +55-11-5681-2400	Facsimile: +55-11-5681-1274/4434
YOKOGAWA MEASURING INSTRUMENTS KOREA CORPORATION (KOREA)	Phone: +82-2-551-0660	Facsimile: +82-2-551-0665
YOKOGAWA AUSTRALIA PTY. LTD. (AUSTRALIA)	Phone: +61-2-9805-0699	Facsimile: +61-2-9888-1844
YOKOGAWA BLUE STAR LTD. (INDIA)	Phone: +91-80-227-1513	Facsimile: +91-80-227-4270
YOKOGAWA MIDDLE EAST E.C. (BAHRAIN)	Phone: +973-358100	Facsimile: +973-336100
LTD. YOKOGAWA ELECTRIC (RUSSIAN FEDERATION)	Phone: +7-095-737-7868	Facsimile: +7-095-737-7869

MCK-ES10